



MFAx - CLOUD FAX SOLUTION

FAXBRIDGE CERTIFICATION



Certification

The device has been tested certified and conforms to FCC and CE standards. All components are RoHS compliant. The unit can be OEM branded if needed.

The following tests have been performed:

Electrostatic Discharge Immunity
 RF Electronic Magnetic Field Immunity
 Electrical Fast Transient Burst
 Variable Surge Test Immunity
 Immunity to Conducted Disturbances
 Voltage Dips and Interruption Immunity

Testing standards:

EN 55022: 2206
 EN 55024: 1998+A1
 EN 55024: 2001+A2
 EN 55024: 2003
 EN 60951: 2006
 EN 60952: 2014

Data Sheet

Physical interfaces

- RJ11 Fax
- MachineRJ11 FXS
- DeviceFTDI
- Management

Indicator lights

- Phone/Fax line
- Power state
- System status
- Ethernet link

Power options

- 5V DC External
- 5V DC Internal

Physical operating environment

- 41 to 114F
- 5 to 45C
- 10 to 90RH

Data Sheet

Physical dimensions	• 5.5" x 4.25" x 0.9" (unit) • 5.75" x 8.75" x 1.75" (box) • 2.7oz (raw weight)
Power options	• 5V DC External • 5V DC Internal
Fax protocol support	• V.34, V.17, V.29, V.27, V.21 • MH, MR, MMR • ECM Capable
Operating system	• Embedded Linux-based kernel • 256MB NAND • 64MB RAM • 8MB Flash
Network configuration	• Static IP Address • DHCP Client
Remote provisioning	• Automatic via HTTPS Firmware • Updatable System Image
Device identification	• Provisioned UID • MAC based UID
Remote diagnosis	• Telnet SSH HTTP, HTTPS • TFTP, FTP, SysLog

Heard enough?

Get started today.



Contact us at sales@documo.com or
call us at (858) 299-5295